

Selwood Drainer 'D' Pump



D100

Specification

Capacity	m ³ /h	120
Total Head	m	26
Max. Solids Size	mm	29
Self Priming Lift	m	8.8
Air Handling	l/s	4.25
Selprime, Absorbs	kW	0.9
Power Required	kW	6.5
Pump Speed Max.	rpm	2000
Pump Speed Min.	rpm	955
Impeller Type	Drainer	
Impeller Blades	3	
Impeller Dia.	mm	192
Inlet Port	mm	DN 100 PN6
Outlet Port	mm	DN 100 PN6
Fuel Tank Capacity*	ltrs	105 Skid 80 Super Silent
Fuel Consumption BEP	lt/hr	1.7

* Fuel tank capacity can be increased with the addition of an auxiliary fuel tank.

Priming Method



The unique original Selwood self priming system utilising a water tolerant diaphragm air pump. An environmentally friendly design that has none of the problems of oil vapour emissions and oil emulsification associated with other priming systems.

Pump Materials



Pump Casing	Grey Iron BSEN 1561 Grade EN-GJL-250
Impeller	Cast Iron BSEN 1563 Grade EN-GJS-450-10
Wear Plates	Cast Iron BSEN 1563 Grade EN-GJS-600-3
Shaft	Steel BS970 Grade 212M36/212M44
NRV Body	Grey Iron BSEN 156 Grade EN-GJL-250
Mechanical Seal	Ceramic / Sealide
Pump End Bearing	Ball
Drive End Bearing	Cylindrical Roller

Prime Movers

Diesel Engine Isuzu 2CA1

Electric motors available

Standard Weights & Measures

 (Pt No. 0912228000)	Skid*	Length	192 cm
		Width	100 cm
		Height	129 cm
		Dry Weight	1015 kg
		Gross Weight	1103 kg
		LWA	101
 (Pt No. 0912156540)	Super Silent	Length	176 cm
		Width	107 cm
		Height	152 cm
		Dry Weight	942 kg
		Gross Weight	1009 kg
		LWA	80
		db(A)@ 7m	58

* Open sets exclude fittings

Optional Extras

- Auto stop-start controls
- Telemetry system
- Oil drain service kit
- Auxiliary fuel tank connectors
- Chalwyn valve spark arrester

Selwood Limited, Bournemouth Road,
Chandler's Ford, Eastleigh, Hampshire, SO53 3ZL. UK
Tel: +44(0) 23 8025 0137 Fax: +44(0) 23 8027 1012
E-mail: pumpsales@selwoodpumps.com
Web: www.selwoodpumps.com

