

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONSTRUCTION	INDUSTRIAL
Stock No		SP 9124	Retail Price
Manufacturer		PRIMAX	Date In Stock
Model		XH100	Year of Manufacture
Serial No		0617121-1	CHASSIS
PUMP DATA		Open/ Skid	SKID
Max Flow		82l/s (295m ³ /h)	Sound Attenuated
Max Head		185m	Length
Suction Size - mm		6" DN150	Width
Discharge Coupling Type		FEMALE BAUER	Height
Discharge Size - mm		6" DN150	Colour
Discharge coupling Type		PN16 FLANGE	Condition
Discharge Detail NRV/Gate/Gauge		FLAP NRV, BUTTERFLY VALVE, PRESSURE GAUGE	AWAITING WORKSHOP ASSESSMENT
Shaft Seal – Mech /Packing		MECHANICAL SEAL	LIFTING DATA/ CHASSIS
Pump Speed Min/Max		1400-1800rpm	Weight Kg
Impeller Type – Open/Closed		CLOSED	Centre Point
Impeller Size		560mm OD	Corner
Solids Handling - mm		22mm IN SUSPENSION	
Others – Stages			Forklift
Material			Trailer – Road tow
Priming Type Comp/vac/ventr		COMPRESSOR	Trailer – Site tow
Long/Close Coupled Pump		CLOSE	Tow Bar Type
Belt Drive		TMING BELT FOR COMPRESSOR	
ENGINE DATA		Size - Dimensions	ESTIMATED 3500 x 1500 x 340mm
Manufacturer		CUMMINS	Capacity
Model		QSM11	Gauge
Serial No		35281466	Bunded
Hours		TBC	Chassis
Exhaust Type			Free Standing
Bellows			Special
Voltage		24V	STARTER PANEL – MODEL: MURPHY
Battery Type			Key / Button
Battery Isolator		YES	Hour Meter
Water Jacket Heater KW			Oil Pressure
Cooling – Air – Rad - Exc		Water cooled rad	Water Temp
ELECTRIC MOTOR N/A		Water Pressure	
Make			Water Vacuum
Voltage			SPEED SELECTOR SWITCH
KW			Special
Amps			TESTING
Cooling			Duration
Speed			Curve On File
Foot / Flange			Photos – Numbers
Starter Type			