

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONSTRUCTION	INDUSTRIAL
Stock No		SP9166	Retail Price
Manufacturer		WARMAN	Date In Stock
Model		6x4 D-AH	Year of Manufacture
Serial No		WP23001	CHASSIS
PUMP DATA		Open/ Skid	OPEN
Max Flow		300m ³ /h	Sound Attenuated
Max Head		35m	Length
Suction Size - mm		DN150 / 6"	Width
Suction Flange BSP Coupling		4 HOLE FLANGE 300 PCD	Height
Discharge Size - mm		DN100 / 4"	Colour
Discharge Detail Flange - BSP		4 HOLE 240 PCD	Condition
Discharge Detail NRV- Gate		NO	
Discharge Pressure Gauge		NO	LIFTING DATA/ CHASSIS
Shaft Seal – Mec /Packing			Weight Kg
Pump Speed		1250rpm	Centre Point
Impeller Type – Open/Closed			Corner
Impeller Size			2x LIFTING EYES ON MOTOR
Solids Handling - mm			Forklift
Others – Stages			Trailer – Road tow
Material		HARD IRON IMPELLER	Trailer – Site tow
Priming Type			Tow Bar Type
Long/Close Coupled Pump		BELT DRIVEN	
Belt Drive		2x V-BELT	FUEL TANK DATA N/A
ENGINE DATA N/A		Size - Dimensions	
Manufacturer			Capacity
Model			Gauge
Serial No			Bunded
Hours			Chassis
Exhaust Type			Free Standing
Bellows			Special
Voltage			STARTER PANEL N/A
Battery Type			Key / Button
Battery Isolator			Hour Meter
Water Jacket Heater KW			Oil Pressure
Cooling – Air – Rad - Exc			Water Temp
ELECTRIC MOTOR		Water Pressure	
Make		BROOK CROMPTON	Water Vacuum
Voltage		380Δ / 660Y	
KW		37kw / 50hz	Special
Amps		71 / 41	TESTING
Cooling		TEFC	Duration
Speed		1470rpm	Curve On File
Foot / Flange			Photos – Numbers
Starter Type			