

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONSTRUCTION	✓	INDUSTRIAL	✓
Stock No		SP6457	Retail Price	P.O.A	
Manufacturer		SYKES	Date In Stock	OCT 2014	
Model		GP150M (SP60)	Year of Manufacture	TBC	
Serial No		M102934	CHASSIS		
PUMP DATA			Open/ Skid	OPEN	
Max Flow		90l/S	Sound Attenuated	NO	
Max Head		38m	Length	2400mm	
Suction Size - mm		6" 150mm	Width	1430mm	
Suction Flange BSP Coupling		6" female bauer	Height	1710mm	
Discharge Size - mm		6" 150mm	Colour	Blue	
Discharge Detail Flange - BSP		6" male bauer	Condition	GOOD USED	
Discharge Detail NRV- Gate		ball type	LIFTING DATA/ CHASSIS		
Discharge Pressure Gauge		Non	Weight Kg	Empty 1150KG 1238KG with fuel.	
Shaft Seal – Mec /Packing		seal	Centre Point	YES	
Pump Speed		1800rpm	Corner	NO	
Impeller Type – Open/Closed		OPEN	Forklift	NO	
Impeller Size		290mm	Trailer – Road tow	NO	
Solids Handling - mm		52mm	Trailer – Site tow	YES 4 wheel	
Others – Stages		Sykes Univac Vacuum System	Tow Bar Type	Hook Tow	
Material			FUEL TANK DATA		
Priming Type		Auto Prime	Size - Dimensions	W=2300mm L=950mm H=3700mm	
Long/Close Coupled Pump		CLOSE	Capacity	120L max 24H, cleaning and flush system	
Belt Drive		On vac pump	Gauge	NO	
ENGINE DATA			Bunded	NO	
Manufacturer		Lister – Petter	Chassis	YES	
Model		TR3	Free Standing	NO	
Serial No		00086703TR3A913	Special		
Hours		2761	STARTER PANEL N/A		
Exhaust Type		Coupled open	Key / Button	Key with pre/heat run / start	
Bellows		NO	Hour Meter	YES	
Voltage		12V	Oil Pressure	Red warning light	
Battery Type		Standard	Water Temp	Red warning light	
Battery Isolator		NO	Water Pressure	Red warning light	
Water Jacket Heater KW		NO	Water Vacuum	Red warning light	
Cooling – Air – Rad - Exc		AIR	ELECTRIC MOTOR N/A		
Make		N/A	TESTING		
Voltage			Duration		
KW			Curve On File		
Amps			Photos – Numbers		
Cooling					
Speed					
Foot / Flange					
Starter Type					