

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONSTRUCTION	INDUSTRIAL
Stock No		SP9002	Retail Price
Manufacturer		GODWIN	Date In Stock
Model		HL100M	Year of Manufacture
Serial No		S496939/02	CHASSIS
PUMP DATA		Open/ Skid	OPEN
Max Flow		125m ³ /h	Sound Attenuated
Max Head		45m	Length
Suction Size - mm		4" / DN100	Width
Suction Flange BSP Coupling		FEMALE BAUER	Height
Discharge Size - mm		4" / DN100	Colour
Discharge Detail Flange - BSP		PN16 FLANGE	Condition
Discharge Detail NRV- Gate		BALL CHECK	
Discharge Pressure Gauge		NO	LIFTING DATA/ CHASSIS
Shaft Seal – Mec /Packing			Weight Kg
Pump Speed		1450rpm	Centre Point
Impeller Type – Open/Closed			Corner
Impeller Size			
Solids Handling - mm			Forklift
Others – Stages			Trailer – Road tow
Material			Trailer – Site tow
Priming Type		COMPRESSOR PRIME	Tow Bar Type
Long/Close Coupled Pump		CLOSE	
Belt Drive			FUEL TANK DATA
ENGINE DATA N/A		Size - Dimensions	
Manufacturer			Capacity
Model			Gauge
Serial No			Bunded
Hours			Chassis
Exhaust Type			Free Standing
Bellows			Special
Voltage			STARTER PANEL
Battery Type			Key / Button
Battery Isolator			Hour Meter
Water Jacket Heater KW			Oil Pressure
Cooling – Air – Rad - Exc			Water Temp
ELECTRIC MOTOR		Water Pressure	
Make			Water Vacuum
Voltage		415v	
KW		22Kw	Special
Amps			TESTING
Cooling		TEFC	Duration
Speed		1450rpm	Curve On File
Foot / Flange			Photos – Numbers
Starter Type		Not included	