

SURFACE PUMP DATA INFORMATION

PUMP TYPE	FIRE	CONSTRUCTION	✓	INDUSTRIAL	✓
Stock No		SP3434		Retail Price	
Manufacturer		SYKES		Date In Stock	MAY 2014
Model		UNIVAC 3		Year of Manufacture	
Serial No				CHASSIS	
PUMP DATA				Open/ Skid	OPEN
Max Flow		65m ³ /h		Sound Attenuated	NO
Max Head		25m		Length	1321mm W/TOWBAR RETRACTED
Suction Size - mm		3"/75mm		Width	990mm
Suction Flange BSP Coupling		3" FEMALE BAUER		Height	1346mm
Discharge Size - mm		3"/75mm		Colour	
Discharge Detail Flange - BSP		3" MALE BAUER		Condition	
Discharge Detail NRV- Gate		NRV		LIFTING DATA/ CHASSIS	
Discharge Pressure Gauge		INTEGRAL		Weight Kg	457kg DRY
Shaft Seal – Mec /Packing		PACKING		Centre Point	
Pump Speed				Corner	NO
Impeller Type – Open/Closed		3 BLADE OPEN		Forklift	NO
Impeller Size		191mm		Trailer – Road tow	2 WHEEL
Solids Handling - mm		50mm		Trailer – Site tow	
Others – Stages				Tow Bar Type	PIN HITCH
Material					
Priming Type		VACUUM PUMP			
Long/Close Coupled Pump		CLOSE			
Belt Drive		BELT DRIVEN VACUUM PUMP		FUEL TANK DATA	
ENGINE DATA				Size - Dimensions	900 x 450 x 150mm ESTIMATE
Manufacturer		LISTER		Capacity	
Model		SR1		Gauge	NO
Serial No				Bunded	NO
Hours				Chassis	YES
Exhaust Type				Free Standing	
Bellows				Special	
Voltage				STARTER PANEL N/A	
Battery Type		HAND CRANK STARTING		Key / Button	
Battery Isolator				Hour Meter	
Water Jacket Heater KW		NO		Oil Pressure	
Cooling – Air – Rad - Exc		AIR		Water Temp	
ELECTRIC MOTOR N/A				Water Pressure	
Make				Water Vacuum	
Voltage					
KW				Special	
Amps				TESTING	
Cooling				Duration	
Speed				Curve On File	
Foot / Flange				Photos – Numbers	
Starter Type					