

Stuart Pumps offer a robust, lightweight box canopy with SPP's proven Vacuum pump primed Q series dewatering pump mounted inside. Fully enclosed and ideal in applications which include general purpose dewatering, over pumping, sewer by-pass, industrial and municipal pumping where reliable prime and re-prime is required with minimal operator interface.



DESIGN FEATURES:

- 110% Bunded for all fluids
- Chassis integral fuel tank for at least 24hours running
- Forklift pockets and central lifting eye available
- Capricorn Starter panel with external vacuum and pressure gauges .
- Battery isolator and exterior E-stop
- 65cfm Vacuum Pump with coalescer and air filtered before exhaust to atmosphere
- Reliable double mechanical seals running in oil bath for continuous dry running
- <65dBA at 7m sound attenuated stackable box canopy offered

PUMP SPECIFICATIONS:

Flow Rate	380 m ³ /h Maximum	Shaft Seal	Silicon Carbide/Silicon Carbide	
Discharge Head	25 m Maximum	Elastomer	Viton	
Working Pressure	10 bar Maximum	Starting	12 Volt Battery by Push Button	
Suction Hose Size	150mm (6") Dia.	Diesel Engine	Perkins 403D	
Discharge Hose Size	150mm (6") Dia.	Sound Pressure Level	<65dBA at 7m	
Max Solids Size	65 mm Diameter x 80mm	Fuel Tank Capacity	TBC	
Pump Casing	Cast Iron	<p>Enquire with our pump sales team about availability on Email: pumpsales@stuartgroup.info Freephone: 0500 459 876 Or direct on: 01953 458988</p>		
Impeller	SG Iron			
Pump Shaft	Stainless Steel			
Wear Plates	SG Iron			
Suction Sump	Cast Iron			